



## INDUSTRIAL HIGH VELOCITY BLOWERS



MOTOR: 1-Phase, 1/2 or 1 HP, single speed, ball bearing,

TEAO, automatic thermal protection

MOUNTING OPTIONS: Wall and ceiling GUARD: Spiral, wire front and rear guards



| TPI MODEL<br>NUMBER | BLADE<br>SIZE | MOTOR<br>TYPE | WATTS | CFM MAX<br>VELOCITY | MOTOR<br>HP | CFM / RPM   | AMPS | PRICE  |
|---------------------|---------------|---------------|-------|---------------------|-------------|-------------|------|--------|
| HV18-208/240V       | 18"           |               | 373   | 3,000 CFM           | 1/2         | 3000 / 1725 | 2.6  | \$583  |
| HV24-208/240V       | 24"           | Direct        |       | 5,290 CFM           |             | 5290 /1725  |      | \$736  |
| HV30-208/240V       | 30"           | Drive         | 746   | 9,000 CFM           | 1           | 9000 / 1700 | 4.7  | \$1065 |
| HV30-480V           | 30"           |               | 746   |                     |             |             | 2.1  | \$1065 |

Other voltages available



#### COMMERCIAL CIRCULATORS

Pedestal & Wall Mount

MOTOR: 1/4 HP, 3 Speed, 120V, 1-Phase, ball-bearing,

open ventilated, permanently lubricated,

permanent split capacitor

SWITCH: Pull Chain

CORD: 9' long SJT type 3 conductor GUARD: Coated steel with retaining clips POLE: Adjusts center of fan from 43" to 60"





CACU30-W

| TPI MODEL<br>NUMBER | BLADE<br>SIZE | MOTOR<br>TYPE | FAN TYPE        | FAN<br>MOUNT | MOTOR<br>HP | CFM MAX<br>VELOCITY | AMPS | PRICE |
|---------------------|---------------|---------------|-----------------|--------------|-------------|---------------------|------|-------|
| CACU30-W            | 30"           | Open          | Non-Oscillating | Wall         | 1/4 HP      | 6,700 CFM           | 2.4  | \$206 |
| CACU30-P            |               | Ventilated    |                 | Pedestal     |             |                     | 2.4  | \$230 |

#### INDUSTRIAL MOUNTED WORKSTATION FAN

MOTOR: 3-Speed, 120V, single phase, sleeve-bearing,

totally enclosed, permanently lubricated, PSC type

SWITCH: Pull Chain

CACU30-P

CORD: 10' long SJT type 3 conductor

GUARD: Spiral coated steel wire, FDA white/gray



| c (List | US  |
|---------|-----|
| Inter   | tek |

| TPI MODEL<br>NUMBER | BLADE<br>SIZE | MOTOR<br>TYPE       | MOTOR HP | CFM MAX<br>VELOCITY | COVERAGE<br>SQ. FT. | AMPS | PRICE |
|---------------------|---------------|---------------------|----------|---------------------|---------------------|------|-------|
| U-18TE              | 18"           | Totally<br>Enclosed | 1/8 HP   | 2,900 CFM           | 125                 | 2.2  | \$120 |



#### **MARTIN SUPPLY LOCATIONS**

TUSCALOOSA / NASHVILLE / DECATUR / ANNISTON / JACKSON, TN / BIRMINGHAM / MEMPHIS / ATLANTA / SHEFFIELD, AL / TUPELO / GREENVILLE, SC / EVANSVILLE, IN / FORT WAYNE, IN / HENDERSON, KY / COLUMBUS, OH / IRMO, SC







### PORTABLE EVAPORATIVE COOLER

MOTOR: Variable speed CORD: 15' long cordset

Four heavy-duty casters WHEELS:

HOUSING: Durable polyethylene black housing



| TPI MODEL<br>NUMBER | EFFECTIVE<br>SQ. FT. | CFM    | VELOCITY<br>(MPH) | INTERNAL<br>WATER<br>(GAL) | FAN<br>BLADE | AMPS | WT<br>(LBS) | SPEEDS   | PRICE  |
|---------------------|----------------------|--------|-------------------|----------------------------|--------------|------|-------------|----------|--------|
| EVAP36HD            | 3,125                | 12,500 | 25                | 60                         | 36"          | 15   | 267         | Variable | \$3320 |

### INDUSTRIAL ASSEMBLED CIRCULATOR HEAD

MOTOR: 2 Speed, 120V, 1-Phase, ball-bearing, totally enclosed,

permanently lubricated, permanent split capacitor

SWITCH: Pull Chain

CORD: 12' long SJT type 3 conductor

GUARD: Coated steel





| TPI MODEL<br>NUMBER | BLADE SIZE | MOTOR<br>TYPE       | FAN HEAD<br>TYPE | CFM MAX<br>VELOCITY | COVERAGE<br>SQ. FT. | AMPS | PRICE |
|---------------------|------------|---------------------|------------------|---------------------|---------------------|------|-------|
| ACH24               | 24"        | Totally<br>Enclosed | Stationary       | 6,000 CFM           | 240                 | 2.5  | \$220 |



**ACH 24** 



# INDUSTRIAL UNASSEMBLED CIRCULATOR

MOTOR: 1/4 HP, 2 Speed, 120V, 1-Phase, ball-bearing, totally enclosed,

permanently lubricated, permanent split capacitor

SWITCH: Pull Chain

CORD: 12' long SJT type 3 conductor

**GUARD:** Coated steel

POLE: Adjusts center of fan from 52" to 78"



TPI MODEL **BLADE MOTOR FAN MOTOR CFM MAX FAN TYPE** AMPS PRICE **VELOCITY NUMBER** SIZE **TYPE MOUNT** HP Totally ACU30-P 30" Pedestal 1/4 HP 4.300 CFM 2.7 Non-Oscillating \$279 **Enclosed** 

# COMMERCIAL PORTABLE BLOWER

MOTOR: 2-Speed, 120V, 1-Phase, ball-bearing, totally enclosed, permanently lubricated

CORD: 8' long SJT type 3 conductor

WHEELS: 5" rubber

**HOUSING: Powder coated 20 gauge steel** 





| TPI MODEL<br>NUMBER | MOTOR<br>TYPE | MOTOR<br>HP | BLADE<br>SIZE | CFM<br>(MAX) | AMPS | PRICE |
|---------------------|---------------|-------------|---------------|--------------|------|-------|
| CPB42-B             | Belt Drive    | 1/2         | 42"           | 7,600        | 6.5  | \$515 |

#### MARTIN SUPPLY LOCATIONS

TUSCALOOSA / NASHVILLE / DECATUR / ANNISTON / JACKSON, TN / BIRMINGHAM / MEMPHIS / ATLANTA / SHEFFIELD, AL / TUPELO / GREENVILLE, SC / EVANSVILLE, IN / FORT WAYNE, IN / HENDERSON, KY / COLUMBUS, OH / IRMO, SC