


HAND SIGNALS FOR CRANE OPERATION

STOP

With an arm extended horizontally to the side, palm down, arm is swung back and forth



EMERGENCY STOP

With both arms extended horizontally to the side, palms down, arms are swung back and forth



SWING


HOIST

With upper arm extended to the side, forearm and index finger pointing straight up, hand and finger make small circles



RAISE BOOM

With arm extended horizontally to the side, thumb points up with other fingers closed



SWING

With arm extened horizontally, index finger points in direction that boom is to swing

RETRACT TELESCOPING BOOM

With hands to the front at waist level, thumbs point at each other with other fingers closed



RAISE THE BOOM & LOWER THE LOAD


With arm extended horizontally to the side and thumb pointing up, fingers open and close while load movement is

desired




DOG EVERYTHING

Hands held together at waist level




LOWER

With arm and index finger pointing down, hand and finger make small circles



LOWER BOOM

With arm extended horizontally to the side, thumb points down with other fingers closed.




EXTEND TELESCOPING BOOM

With hands to the front at waist level, thumbs point outward with other fingers closed



TRAVEL/ TOWER TRAVEL

With all fingers pointing up, arm is extended horizontally out and back to make a pushing motion in the direction of travel






HAND SIGNALS FOR CRANE OPERATION


LOWER THE BOOM & RAISE THE LOAD

With arm extened horizontally to the side and thumb pointing down, fingers open and close while load movement is desired



MOVE SLOWLY

A hand is placed in front of the hand that is giving the action signal



USE AUXILLARY HOIST (WHIPLINE)

With arm bent at elbow and forearm vertical, elbow is tapped with other hand. Then regular signal is used to indicate desired action



CRAWLER CRANE TRAVEL, BOTH TRACKS

Rotate fists around each other in front of body; direction of rotation away from body indicates travel forward; rotation towards body indicated travel backward




USE MAIN HOIST

A hand taps on top of the head. Then regular signal is given to indicate desired action



TROLLY TRAVEL

With palm up, fingers closed and thumb pointing in direction of motion, hand is jerked horizontally in direction trolley is to travel



Source for hand signals: OSHA 29 CFR 1926, Subpart CC, Appendix A