

FOR DEMANDING WORK ENVIRONMENTS

■ *jalas*® HEAVY DUTY 1278

A tough, mid-cut safety shoe with highest protection level (S3) and BOA® Fit System built for heavy work. The PU-coated leather and microfibre upper gives excellent foot protection and additional ankle support. The oil and heat-resistant nitrile outer sole gives excellent grip, and JALAS® Composite Toe Cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD® mean safer workdays.

NAIL PROTECTION MATERIAL Steel

FITTING Regular

FASTENING BOA® Fit System

SIZE RANGE 35-48

UPPER MATERIAL PU-coated leather

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

LINING MATERIAL Polyester, polyamide



EN ISO 20345:2011
S3, SRC, CI, HRO, HI

ASTM F2413-18
M/II/C
SD 35 PR



■ *jalas*® HEAVY DUTY 1358

A tough, water-repellent mid-cut safety boot featuring highest (S3) protection with unique BOA® Fit System. PU-coated leather and microfibre upper has excellent foot support and certified ankle impact protection. An oil and heat-resistant Vibram Arctic Grip outer sole gives steady feet in slippery conditions. JALAS® Composite Toe Cap, plasma-treated puncture protection and double impact protection zones in PORON® XRD®.

NAIL PROTECTION MATERIAL Plasma-treated

composite (PTC) textile

FITTING Regular

FASTENING BOA® Fit System

SIZE RANGE 35-48

UPPER MATERIAL PU-coated leather, Microfiber

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL HNB rubber + Gripper lugs

LINING MATERIAL Technical fleece



EN ISO 20345:2011
S3, SRC, HRO, M, CI, HI, AN

ASTM F2413-18
M/II/C
Mt SD 35 PR



■ *jalas*® HEAVY DUTY 1378

A fully lined winter safety boot with highest (S3) protection designed for very cold or slippery conditions. The PU-coated leather, and faux-fur and Thinsulate™ lining mean feet are protected in any conditions. The oil and heat-resistant Vibram Arctic Grip sole provides outstanding grip, and JALAS® Composite Toe Cap, steel puncture protection and double impact protection zones in PORON® XRD®.

NAIL PROTECTION MATERIAL Steel

FITTING Regular

FASTENING Laces

SIZE RANGE 35-48

UPPER MATERIAL PU-coated leather

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

LINING MATERIAL Polyester fur, Thinsulate™



EN ISO 20345:2011
S3, SRC, CI, HRO

ASTM F2413-18
M/II/C
SD 35 PR

