





INDUSTRIAL HIGH VELOCITY BLOWERS

MOTOR: 1-Phase, 1/2 or 1 HP, single speed, ball bearing, TEAO, automatic thermal protection **MOUNTING OPTIONS: Wall and ceiling** GUARD: Spiral, wire front and rear guards



TPI MODEL NUMBER	BLADE SIZE	MOTOR TYPE	WATTS	CFM MAX VELOCITY	MOTOR HP	CFM / RPM	AMPS	PRICE
HV18-208/240V	18"		070	3,000 CFM	1/2	3000 / 1725	0.6	\$885
HV24-208/240V	24"	Direct	373	5,290 CFM		5290 /1725	2.6	\$1015
HV30-208/240V	30"	Drive	746	0.000 OFM		0000 / 1700	4.7	\$1466
HV30-480V	30"		/40	9,000 CFM		9000 / 1700	2.1	\$1466

Other voltages available



COMMERCIAL CIRCULATORS Pedestal & Wall Mount MOTOR: 1/4 HP, 3 Speed, 120V, 1-Phase, ball-bearing, open ventilated, permanently lubricated, permanent split capacitor SWITCH: Pull Chain CORD: 9' long SJT type 3 conductor GUARD: Coated steel with retaining clips POLE: Adjusts center of fan from 43" to 60"



CACU30-W

TPI MODEL NUMBER	BLADE SIZE	MOTOR TYPE	FAN TYPE	FAN MOUNT	MOTOR HP	CFM MAX VELOCITY	AMPS	PRICE
CACU30-W	30"	Open Ventilated	Non-Oscillating	Wall	1/4 HP	6,700 CFM	2.4	\$291
CACU30-P				Pedestal				\$365

Intertek

INDUSTRIAL MOUNTED WORKSTATION FAN

- MOTOR: 3-Speed, 120V, single phase, sleeve-bearing, totally enclosed, permanently lubricated, PSC type SWITCH: Pull Chain
- CORD:
- 10' long SJT type 3 conductor GUARD: Spiral coated steel wire, FDA white/gray

TPI MODEL NUMBER	BLADE SIZE	MOTOR TYPE	MOTOR HP	CFM MAX VELOCITY	COVERAGE SQ. FT.	AMPS	PRICE
U-18TE	18"	Totally Enclosed	1/8 HP	2,900 CFM	125	2.2	\$169



ALABAMA - TUSCALOOSA, DECATUR, ANNISTON, BIRMINGHAM, SHEFFIELD TENNESSEE - NASHVILLE, JACKSON, MEMPHIS INDIANA - EVANSVILLE, FORT WAYNE, FRANKLIN, BLOOMINGTON, FERDINAND, MUNCIE SOUTH CAROLINA - GREENVILLE, COLUMBIA MISSISSIPPI - JACKSON

MARTIN



INDUSTRIAL ASSEMBLED CIRCULATOR HEAD

MOTOR:	2 Speed, 120V, 1-Phase, ball-bearing, totally enclosed, permanently lubricated, permanent split capacitor
CORD:	Pull Chain 12' long SJT type 3 conductor Coated steel





TPI MODE NUMBER	BLADE SIZE	MOTOR TYPE	FAN HEAD TYPE	CFM MAX VELOCITY	COVERAGE SQ. FT.	AMPS	PRICE
ACH24	24"	Totally Enclosed	Stationary	6,000 CFM	240	2.5	\$303

INDUSTRIAL UNASSEMBLED CIRCULATOR

MOTOR: 1/4 HP, 2 Speed, 120V, 1-Phase, ball-bearing, totally enclosed, permanently lubricated, permanent split capacitor SWITCH: Pull Chain

CORD: 12' long SJT type 3 conductor

GUARD: Coated steel

POLE: Adjusts center of fan from 52" to 78"



ACU 30-P

TPI MODEL NUMBER	BLADE SIZE	MOTOR TYPE	FAN TYPE	FAN MOUNT	MOTOR HP	CFM MAX VELOCITY	AMPS	PRICE
ACU30-P	30"	Totally Enclosed	Non-Oscillating	Pedestal	1/4 HP	4,300 CFM	2.7	\$399

COMMERCIAL PORTABLE BLOWER

CORD: WHEELS:	tota 8' lo 5" i	peed, 120V, 1-I ally enclosed, ong SJT type 3 rubber wder coated 20	permanentl conductor	y lubricat	ed	
	- I I	MOTOD	MOTOD	BLADE		

TPI MODEL NUMBER	MOTOR TYPE	MOTOR HP	BLADE SIZE	CFM (MAX)	AMPS	PRICE
CPB42-B	Belt Drive	1/2	42"	7,600	6.5	\$616



MARTIN SUPPLY LOCATIONS

ALABAMA - TUSCALOOSA, DECATUR, ANNISTON, BIRMINGHAM, SHEFFIELD TENNESSEE - NASHVILLE, JACKSON, MEMPHIS INDIANA - EVANSVILLE, FORT WAYNE, FRANKLIN, BLOOMINGTON, FERDINAND, MUNCIE SOUTH CAROLINA - GREENVILLE, COLUMBIA MISSISSIPPI - JACKSON

MARTINSUPPLY.COM 800-828-8116