

## PMXSLIM® ANSI • CE •



ADJUSTABLE  
NOSEPIECE



CO-INJECTED  
TEMPLES

Slim fit for smaller facial features // Soft adjustable nosepiece // Co-injected temple design includes soft rubber tips for a non-slip fit // Custom imprinting available

### Black Temples | 6 Variations

- SB7110S ● Clear
- SB7110ST ● Clear **H2X AF**
- SB7120S ● Gray
- SB7120ST ● Gray **H2X AF**
- SB7138S ● Sandstone Bronze
- SB7180S ● I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB7110S	P Z87 + U6	P Z87 +	Weight: 25 gm	Lens: polycarbonate
SB7110ST	P Z87 + U6	P Z87 +	PD: 68 mm	Frame: polycarbonate
SB7120S	P Z87 + U6 L2.5	P Z87 +	Bridge: 14.5 mm	Temples: polycarbonate & thermoplastic elastomers
SB7120ST	P Z87 + U6 L2.5	P Z87 +	Lens base: 10 curve	Hinge: polycarbonate
SB7138S	P Z87 + S	P Z87 +	Lens size diagonal: 137.7 mm	Screw: stainless steel
SB7180S	P Z87 + U6 L1.7	P Z87 +	Lens size vertical: 45 mm	Side shields: polycarbonate
			Lens thickness: 2.3 mm	Nosepiece: polyvinyl chloride
			Overall length (lens - tip): 170 mm	
			Overall width (hinge - hinge): 129 mm	
			Closest point between temple tips: 86 mm	
			Closest point between lens: 9 mm	

  

<h4>Lens Marking Symbols</h4> <p>P: Manufacturer's mark</p> <p>Z87: ANSI standard for eye and face protection devices</p> <p>+: High impact</p> <p>S: Special purpose</p> <h4>UV Filter Transmittance</h4> <p>U6: .01% max effective far UV • .1% max near UV</p> <h4>Visible Light Filters</h4> <p>L1.7: 55% Max. Visible Light</p> <p>L2.5: 29% max visible light</p>	<h4>Temple Marking Symbols</h4> <p>P: Manufacturer's mark</p> <p>Z87: ANSI standard for eye and face protection devices</p> <p>+: High impact</p>
---	---